

## PRODUCT DETAILS

### HOLLOW SHAFT GEAR MOTOR

- 1/10 Horse Power (Larger motor if required for size)
- Output RPM: 8
- Top speed 80' per minute
- Sealed gear box

### INVERTER DRIVE

- Intelligent drive system – soft start inverter with Acceleration and Deceleration Capability

### TRACK

- 1-5/16 inches O.D. by 14 Gauge Welded Steel Tubing,
- Zinc Plated Cross Members: 1-1/2" & 2", 14 Gauge Square Tubing

### FRAMES

- IMAC ( Injection Molding Acetyl Copolymer) Frames
- Stamped Steel Yokes with 1-3/8 inch Diameter Load
- Load Bearing Wheels with Nylon Tires
- Hardened Inner Races Roll on Steel Ball Bearings
- Nylon Stabilizing Roller Mounted on Underside of Yoke

### OPERATING CONTROLS

- Bi-Directional Foot Switch
- Conveyor Speed: Variable, adjustable based on need, pre-set at factory

## CONVEYOR WEIGHTS

CONVEYOR	WEIGHT
6'	160
7'	170'
8'	180'
9'	190'
10'	200'
11'	210'
12'	220'
13'	230'
14'	240'
15'	250'
16'	260'
17'	270'
18'	280'
19'	290'
20'	300'
THERE IS NO MAXIMUM LENGTH CONVEYOR	